






## Stanley Rotary Lasers

					
<b>FUNCTION</b>	<b>RL100</b>	<b>RL250</b>	<b>RL250GL</b>	<b>RL350</b>	<b>RL350GL</b>
<b>Accuracy @ ± 100' (30M)</b>	1/4" (6mm)	3/32" (2.4mm)	1/16" (1.6mm)	1/8" (3mm)	1/8" (3mm)
<b>Working Range (indoor/outdoor)</b>	200/800	200/2000	0/2300	200/2000	0/2300
<b>Grade Accuracy @ ± 100' (30M)</b>	1/4" (6mm)	1/4" (6mm)	1/4" (6mm)	1/4" (6mm)	1/4" (6mm)
<b>Vertical Accuracy @ ± 100' (30M)</b>	N/A	N/A	N/A	1/8" (3mm)	1/8" (3mm)
<b>Self-Leveling Mode</b>		X	X	X	X
<b>Manual Mode</b>		X	X	X	X
<b>ADS mode</b>		X	X	X	X
<b>Remote Capable</b>	X			X	X
<b>± 3° Self-Leveling Range</b>					
<b>± 5° Self-Leveling Range</b>		X	X	X	X
<b>635nm High Power Diode</b>	X			X	X
<b>650nm Standard Diode</b>		X	X		
<b>Lay-Down Capable</b>	X			X	X
<b>Grade Dial-Off Dual Axis</b>					
<b>Single Grade Manual- Single Axis</b>		X	X		
<b>Grade Manual- Dual Axis</b>					
<b>Grade Manual- Dual Axis w/Remote</b>				X	X
<b>Variable Speed Rotation</b>				X	X
<b>Fixed Speed Rotation</b>		X	X		
<b>Sweep (fixed selectable)</b>	X			X	X
<b>Sweep (point-to-point)</b>					
<b>Spot Mode</b>				X	X
<b>Plumb Down Beam</b>					
<b>Lay-Down Plumb Beam</b>					
<b>LCD Display</b>					
<b>Cage with Glass</b>					
<b>Cage without Glass</b>	X	X	X	X	X
<b>Warranty</b>	1 YR.	2 YRS.	2 YRS.	2 YRS.	2 YRS.