

Electronic Self-Leveling Horizontal & Vertical Rotary Laser System

Model #: 40-6558
UPC: 049448065585
MSRP: \$1,689.04



Designed for indoor and outdoor applications, Electronically-controlled dual slope feature, Electronic self-leveling horizontally and vertically, Laser beam modes include four adjustable line lengths and three rotational speeds, Three rotational speeds: 0, 300 and 800 RPM, Visual and audible alarms when beyond leveling range, Height of Instrument/Tilt alarm function ensures product accuracy.

PRODUCT DETAILS

- Designed for indoor and outdoor applications
- Electronically-controlled dual slope feature
- Electronic self-leveling horizontally and vertically
- Laser beam modes include four adjustable line lengths and three rotational speeds
- Three rotational speeds: 0, 300 and 800 RPM
- Visual and audible alarms when beyond leveling range
- Height of Instrument/Tilt alarm function ensures product accuracy
- 40-6558 Includes > Laser, Li-ion rechargeable battery pack, alkaline battery compartment (batteries not included), Li-ion battery adapter, remote control with 9V battery, detector with 9V battery and clamp, magnetic target, tinted glasses, aluminum tripod, 13 ft. grade rod, instruction manual with warranty card, hard-shell carrying case



SPECIFICATIONS

Accuracy	+/-1/16"/100ft. (+/-1.5mm/30m)
Auto-Leveling Range	+/- 5 degrees
Battery Life	Approximately 25 hours with Li-ion rechargeable battery pack (included); 16 hours with alkaline batteries (not included)
Center Screw Thread	5/8"-11
Dimensions	8.62" x 6.30" x 7.95" (219 x 160 x 202mm)
Exterior Range	Up to 2000ft. (600m) diameter with detector
Interior Range	Up to 200ft. (60m) diameter depending on light conditions
IP Protection Class	66
Laser Classification	Class IIIa
Laser Wavelength	635nm+/-10nm (Red)
Leveling Method	Automatic (Electronic)
Maximum Power Output	Less than/Equal to 5mW
Power Supply	Li-ion rechargeable battery pack or adapter (included); 3 "C" alkaline batteries (not included)
Remote Range	Up to 200ft. (60m) diameter with remote
Rotation Speeds	0, 300 and 800 RPM
Slope	+/- 5 degrees
Warranty	3 Year Warranty
Working Temperature	14 degrees to 113 degrees (-10 degrees celsius to +45 degrees celsius)

APPLICATION

The Johnson Level 40-6558 can be used for the following indoor and outdoor applications; leveling, checking cut and fill, setting foundations and footings, concrete pours, septic tanks and basement excavations, acoustical ceiling and drywall, align and plumb walls, metal stud and wood framers, level deck floors, establish diagonals and footings, contour framing, drainage, terracing and retaining walls.



For additional information on Johnson products, please contact
Customer Service at 888.953.8357 or service@johnsonlevel.com
www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.