

AQUATRAC³⁰⁰ | Water Leak Detector



KEY FEATURES

- 1 Amplifier w/touchscreen
- 2 Hand-held trigger w/4' cable
- 3 High sensitivity ground sensor
- 4 Hi-fidelity Koss headphones
- 5 3 section contact rod
- 6 Magnet w/screw on base
- 7 User Manual

FEATURES

- ⊕ Touchscreen display
- ⊕ Locates water leaks on plastic pipes at a minimum of 12psi
- ⊕ Three pre-determined frequency filters (low, medium, and high) and customizable frequencies are available through the filters' menu, down to a 10Hz difference between low and high-frequency limits.
- ⊕ Basic and Advance frequency modes display the frequencies on the screen with color bar graphs, making it easy to identify the desired range of frequencies and choose the correct filters.
- ⊕ Hand-held microphone trigger, for safe and accurate listening of water leaks on utility pipes
- ⊕ Rechargeable lithium battery provides the user with long-lasting operation in between charges
- ⊕ Designed for all water leak detection applications, including leak surveys and leak pinpointing. Use the 3-point ground plate for pinpointing on streets and concrete slabs. Use the magnet base or contact rods for leak surveys at hydrants, valves, or meters.
- ⊕ A lightweight device with simple operation and high performance, extremely compact and convenient.
- ⊕ The AquaTrac300 is the perfect solution for the professional water leak detector as well as the occasional locator due to its simplicity of operation that exceeds other leak detectors in the market.
- ⊕ Its ABS custom carrying case ensures the AquaTrac 300 is protected against damage during transportation and it is IP68 rated against water damage as well.

SPECIFICATIONS

AMPLIFIER

- ⊕ Frequency Range: 0 Hz to 5120 Hz
- ⊕ Amplification: 65 dB +/- 4%
- ⊕ Display: 4.25" LCD touchscreen, backlit display
- ⊕ Power & Battery Life: Internal Li-Ion Rechargeable Battery
Up to 20 hours of continuous use
- ⊕ Operating Temperature: 0° to 140° F (-17.8° to 60° C)
- ⊕ Filters: 3 pre-set filters, custom adjustments
- ⊕ Dimensions: 6" x 5" x 4"

HEADPHONES

- ⊕ Koss Model: 60 ohms, 102 dB SPL, 40-20,000 Hz
3.5mm Jack
- ⊕ David Clark Model*: 60 ohms, 99 dB SPL, 6.3mm Jack
**(Optional)*

ABS CARRYING CASE


- ⊕ Weight (full): 15 lbs (6.8 Kg)
- ⊕ Size: 20" x 17" x 8"

Money Back Guarantee!



Includes:

- ⊕ ABS case w/custom foam
- ⊕ Instruction manual



Rev. 01/23/2023



SubSurface Instruments, Inc. | 1230 Flightway Drive, De Pere, WI. 54115
toll free: 855.422.6346 | Website: www.ssilocators.com | email: info@ssilocators.com

